

n-Butyl Alcohol**024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

SECTION 1. IDENTIFICATION

Product name : n-Butyl Alcohol

Number : 000000011398

Product Use Description : Solvent

Manufacturer or supplier's details : Honeywell International Inc.
1953 South Harvey Street
Muskegon, MI 49442

For more information call : 1-800-368-0050
+1-231-726-3171(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : **Medical: 1-800-498-5701 or +1-303-389-1414**
: **Transportation (CHEMTREC): 1-800-424-9300 or**
: **+1-703-527-3887**
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : liquid, clear

Color : colourless

Odor : characteristic alcohol-like

Classification of the substance or mixture

Classification of the substance or mixture : **Flammable liquids, Category 3**
Acute toxicity, Category 4, Oral
Skin irritation, Category 2
Serious eye damage, Category 1
Specific target organ toxicity - single exposure, Category 3,
Respiratory system, Central nervous system

n-Butyl Alcohol**024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

GHS Label elements, including precautionary statements

Symbol(s)

:



Signal word

: **Danger**

Hazard statements

: **Flammable liquid and vapour.**
Harmful if swallowed.
Causes skin irritation.
Causes serious eye damage.
May cause respiratory irritation.
May cause drowsiness or dizziness.

Precautionary statements

: **Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ eye protection/ face protection.

Response:

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER/doctor.
Rinse mouth.
If skin irritation occurs: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

n-Butyl Alcohol**024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Keep cool.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : C₄H₁₀O

Chemical nature : Substance

Chemical name	CAS-No.	Concentration
Butan-1-ol	71-36-3	100.00 %

SECTION 4. FIRST AID MEASURES

- Inhalation : Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician.
- Skin contact : Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Call a physician if irritation develops or persists.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician.
- Ingestion : Do not induce vomiting without medical advice. Immediate

n-Butyl Alcohol**024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

medical attention is required. Never give anything by mouth to an unconscious person. Call a physician.

Notes to physician

Indication of immediate medical attention and special treatment needed, if necessary : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Cool closed containers exposed to fire with water spray.
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.
- Specific hazards during firefighting : Flammable.
Vapours may form explosive mixtures with air.
Vapours are heavier than air and may spread along floors.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide
Carbon dioxide (CO₂)
- Special protective equipment for firefighters : Wear self-contained breathing apparatus and protective suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Wear personal protective equipment. Unprotected persons must be kept away.
Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not swallow.

n-Butyl Alcohol**024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

- Avoid breathing vapours, mist or gas.
Avoid contact with skin, eyes and clothing.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Discharge into the environment must be avoided.
Do not flush into surface water or sanitary sewer system.
Do not allow run-off from fire fighting to enter drains or water courses.
- Methods and materials for containment and cleaning up : Ventilate the area.
No sparking tools should be used.
Use explosion-proof equipment.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE**Handling**

- Precautions for safe handling : Wear personal protective equipment.
Use only in well-ventilated areas.
Keep container tightly closed.
Do not smoke.
Do not swallow.
Avoid breathing vapours, mist or gas.
Avoid contact with skin, eyes and clothing.
- Advice on protection against fire and explosion : Keep away from fire, sparks and heated surfaces.
Take precautionary measures against static discharges.
Ensure all equipment is electrically grounded before beginning transfer operations.
Use explosion-proof equipment.
Keep product and empty container away from heat and sources of ignition.
No sparking tools should be used.
No smoking.

Storage

- Conditions for safe storage, including any : Store in area designed for storage of flammable liquids. Protect from physical damage.

n-Butyl Alcohol**024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep away from heat and sources of ignition.
Keep away from direct sunlight.
Store away from incompatible substances.
Container hazardous when empty.
Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- | | | |
|--------------------------|---|--|
| Protective measures | : | Ensure that eyewash stations and safety showers are close to the workstation location. |
| Engineering measures | : | Use with local exhaust ventilation.
Prevent vapour buildup by providing adequate ventilation during and after use. |
| Eye protection | : | Wear as appropriate:
Safety glasses with side-shields
If splashes are likely to occur, wear:
Goggles or face shield, giving complete protection to eyes |
| Hand protection | : | Solvent-resistant gloves
Gloves must be inspected prior to use.
Replace when worn. |
| Skin and body protection | : | Wear as appropriate:
Solvent-resistant apron
Flame retardant antistatic protective clothing.
If splashes are likely to occur, wear:
Protective suit |
| Respiratory protection | : | In case of insufficient ventilation wear suitable respiratory equipment.
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
Use NIOSH approved respiratory protection. |
| Hygiene measures | : | When using, do not eat, drink or smoke.
Wash hands and face before breaks and immediately after handling the product. |

n-Butyl Alcohol**024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

Keep working clothes separately.
Remove and wash contaminated clothing before re-use.
Do not swallow.
Avoid breathing vapours, mist or gas.
Avoid contact with skin, eyes and clothing.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
Butan-1-ol	71-36-3	TWA : Time weighted average	(20 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values
Butan-1-ol	71-36-3	Ceil_Tim e : Ceiling Limit Value and Time Period (if specified) :	150 mg/m3 (50 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
Butan-1-ol	71-36-3	SKIN_DE S : Skin designation:	Can be absorbed through the skin.	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
Butan-1-ol	71-36-3	PEL : Permissible exposure limit	300 mg/m3 (100 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Butan-1-ol	71-36-3	SKIN_FINAL : Skin designation (Final Rule Limit applies):	Can be absorbed through the skin.	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)

SAFETY DATA SHEET

**n-Butyl Alcohol****024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

Butan-1-ol	71-36-3	Ceiling : Ceiling Limit Value:	150 mg/m3 (50 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
------------	---------	---	-----------------------	------	---

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid, clear
Color	: colourless
Odor	: characteristic alcohol-like
Odor threshold	: Note: no data available
pH	: Note: Not applicable
Melting point/range	: -89 °C
Boiling point/boiling range	: 117 °C
Flash point	: 99 °F (37 °C) Method: closed cup
Evaporation rate	: Note: no data available
Lower explosion limit	: 1.4 %(V)
Upper explosion limit	: 11.2 %(V)
Vapor pressure	: 8.67 hPa at 25 °C(77 °F)
Vapor density	: 2.55 Note: (Air = 1.0)
Density	: 0.81 g/cm3 at 20 °C

n-Butyl Alcohol**024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

Water solubility : 78 g/l at 20 °C

Partition coefficient:
n-octanol/water : Note: no data available

Ignition temperature : 343 °C

Decomposition temperature : Note: no data available

Viscosity, dynamic : Note: no data available

Viscosity, kinematic : Note: no data available

Molecular weight : 74.12 g/mol

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous
reactions : Hazardous polymerisation does not occur.Conditions to avoid : Heat, flames and sparks.
Keep away from direct sunlight.Incompatible materials : Oxidizing agents
Strong acids and strong bases
Aluminium
May attack many plastics, rubbers and coatings.Hazardous decomposition
products : In case of fire hazardous decomposition products may be
produced such as:
Carbon monoxide
Carbon dioxide (CO₂)

n-Butyl Alcohol**024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity	: LD50: 790 mg/kg Species: Rat
Acute inhalation toxicity	: LC50: > 17.76 mg/l , vapour Exposure time: 4 h Species: Rat Note: No deaths
Acute dermal toxicity	: LD50: 3,400 mg/kg Species: Rabbit
Skin irritation	: Species: Rabbit Result: Moderate skin irritation
Eye irritation	: Species: Rabbit Result: Severe eye irritation
Repeated dose toxicity	: Species: Rat Application Route: Inhalation Exposure time: 13 Weeks NOAEL (No observed adverse effect level): 3000 ppm : Species: Rat Application Route: Oral Exposure time: 13 Weeks NOAEL (No observed adverse effect level): 125 mg/kg/d LOAEL (Lowest observed adverse effect level): 500 mg/kg/d
Genotoxicity in vitro	: Note: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
Genotoxicity in vivo	: Note: In vivo tests did not show mutagenic effects

n-Butyl Alcohol**024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity effects**

Toxicity to fish : static test
LC50: 1,510 mg/l
Exposure time: 96 h
Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates : EC50: 2,337 mg/l
Exposure time: 24 h
Species: Daphnia magna (Water flea)

: EC50: 1,983 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)

Toxicity to algae : LC50: > 500 mg/l
Exposure time: 48 h
Species: Desmodesmus subspicatus (green algae)

Toxicity to bacteria : EC50: 2,056 mg/l
Exposure time: 5 min
Species: Photobacterium phosphoreum

: EC50: 2,186 mg/l
Exposure time: 30 min
Species: Photobacterium phosphoreum

Elimination information (persistence and degradability)

Biodegradability : Result: Readily biodegradable.
Value: > 70 %

Further information on ecology

Additional ecological information : Do not flush into surface water or sanitary sewer system.

n-Butyl Alcohol**024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 1120
Proper shipping name : BUTANOLS
Class : 3
Packing group : III
Hazard Labels : 3

IATA UN/ID No. : UN 1120
Description of the goods : BUTANOLS
Class : 3
Packaging group : III
Hazard Labels : 3
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355
Packing instruction (passenger aircraft) : Y344

IMDG UN/ID No. : UN 1120
Description of the goods : BUTANOLS
Class : 3
Packaging group : III
Hazard Labels : 3
EmS Number : F-E, S-D
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**Inventories**

US. Toxic Substances Control Act : On TSCA Inventory

n-Butyl Alcohol**024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

Australia. Industrial Chemical (Notification and Assessment) Act : On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI) : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances (IECSC) : On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

US. EPA CERCLA Hazardous Substances (40 CFR 302) : The following component(s) of this product is/are subject to release reporting under 40 CFR 302 when release exceeds the Reportable Quantity (RQ):

Reportable quantity: 5000 lbs
: Butan-1-ol 71-36-3

SARA 302 Components : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components : The following components are subject to reporting levels established by SARA Title III, Section 313:
: Butan-1-ol 71-36-3

n-Butyl Alcohol**024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

CERCLA Reportable Quantity : 5000 lbs

California Prop. 65 : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Massachusetts RTK : Butan-1-ol 71-36-3

New Jersey RTK : Butan-1-ol 71-36-3

Pennsylvania RTK : Butan-1-ol 71-36-3

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 2*	2
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

n-Butyl Alcohol**024-1L**

Version 2.0

Revision Date 06/26/2019

Print Date 05/02/2023

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 04/24/2014

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group