

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

SECTION 1. IDENTIFICATION

Product name : 2-Ethoxyethanol

Number : 000000020530

Product Use Description : Laboratory chemicals

Manufacturer or supplier's details : Honeywell Specialty Chemicals Seelze GmbH
Wunstorfer Straße 40
Seelze, 30926

For more information call : 1-800-368-0050
+1-231-726-3171
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : **Medical: 1-800-498-5701 or +1-303-389-1414**
: **Transportation (CHEMTREC): 1-800-424-9300 or**
: **+1-703-527-3887**
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : liquid

Color : colourless

Odor : ether-like

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

Classification of the substance or mixture

Classification of the substance or mixture : Flammable liquids, Category 3
Acute toxicity, Category 4, Oral
Acute toxicity, Category 3, Inhalation
Reproductive toxicity, Category 1B

GHS Label elements, including precautionary statements

Symbol(s)

:



Signal word

: Danger

Hazard statements

: Flammable liquid and vapour.
Harmful if swallowed.
Toxic if inhaled.
May damage fertility or the unborn child.

Precautionary statements

: **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

protection.

Response:

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER /doctor.

Rinse mouth.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTSFormula : C₄H₁₀O₂

Chemical nature : Substance

Chemical name	CAS-No.	Concentration
2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether)	110-80-5	100.00 %

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

SECTION 4. FIRST AID MEASURES

- General advice : First aider needs to protect himself. Move out of dangerous area. Take off immediately all contaminated clothing.
- Inhalation : If inhaled, remove to fresh air. Call a physician immediately.
- Skin contact : After contact with skin, wash immediately with plenty of water. If symptoms persist, call a physician.
- Eye contact : Rinse thoroughly with plenty of water, also under the eyelids. Remove contact lenses. Protect unharmed eye. Get medical attention immediately.
- Ingestion : When swallowed, allow water to be drunk. Call a physician immediately.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Carbon dioxide (CO₂)
Dry powder
Dry sand
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.
- Specific hazards during firefighting : Flammable.
Vapours may form explosive mixtures with air.
Vapours are heavier than air and may spread along floors.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
Fire may cause evolution of:
Carbon monoxide
Carbon dioxide (CO₂)

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Wear personal protective equipment. Unprotected persons must be kept away.
Ensure adequate ventilation.
Remove all sources of ignition.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up : Ventilate the area.
Do not use sparking tools.
Use explosion-proof equipment.
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE**Handling**

Precautions for safe handling : Wear personal protective equipment.
Use only in well-ventilated areas.

Advice on protection against fire and explosion : Keep product and empty container away from heat and sources of ignition.
No smoking.
Take precautionary measures against static discharges.

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

Vapours may form explosive mixtures with air.

Storage

Conditions for safe storage, including any incompatibilities : Store in area designed for storage of flammable liquids. Protect from physical damage.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Store in original container.
Protect from exposure to air/oxygen (peroxide formation).

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Ensure that eyewash stations and safety showers are close to the workstation location.
Legal requirements are to be considered in regard of the selection, use and care of personal protective equipment.
Avoid exposure - obtain special instructions before use.
Avoid inhalation of vapour or mist.

Engineering measures : Use with local exhaust ventilation.

Eye protection : Safety glasses with side-shields

Hand protection : Impervious butyl rubber gloves
Gloves must be inspected prior to use.
Replace when worn.

Skin and body protection : Protective suit

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Hygiene measures : Take off all contaminated clothing immediately.
Remove and wash contaminated clothing before re-use.
Wash hands before breaks and at the end of workday.
When using do not eat or drink.

2-Ethoxyethanol

128082-1L

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether)	110-80-5	TWA : Time weighted average	(5 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values
2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether)	110-80-5	SKIN_DES : Skin designation:	Can be absorbed through the skin.	2008	ACGIH:US. ACGIH Threshold Limit Values
2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether)	110-80-5	REL : Recommended exposure limit (REL):	1.8 mg/m3 (0.5 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether)	110-80-5	SKIN_DES : Skin designation:	Can be absorbed through the skin.	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether)	110-80-5	PEL : Permissible exposure limit	740 mg/m3 (200 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether)	110-80-5	SKIN_DES : Skin designation:	Can be absorbed through the skin.	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether)	110-80-5	TWA : Time weighted average	740 mg/m3 (200 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether)	110-80-5	SKIN_FI NAL : Skin designati on (Final Rule Limit applies):	Can be absorbed through the skin.	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Color	: colourless
Odor	: ether-like
pH	: Note: neutral
setting point	: -70 °C
Boiling point/boiling range	: ca. 136 °C at 1,013 hPa
Flash point	: 104 °F (40 °C) at 1,013 hPa Method: closed cup
Lower explosion limit	: 1.8 %(V)

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

Upper explosion limit	: 15.7 %(V)
Vapor pressure	: 5.1 hPa at 20 °C(68 °F) 7.51 hPa at 25 °C(77 °F)
Vapor density	: 3.11 Note: (Air = 1.0)
Density	: 0.93 g/cm ³ at 20 °C
Water solubility	: Note: completely miscible
Partition coefficient: n-octanol/water	: log Pow: 0.32
Ignition temperature	: 235 °C at 1,013 hPa
Decomposition temperature	: Note: At normal pressure may be distilled without decomposition.
Viscosity, dynamic	: 1.84 mPa.s at 25 °C
Molecular weight	: 90.12 g/mol

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: Stable under recommended storage conditions.
--------------------	--

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

Possibility of hazardous reactions : Reacts with air to form peroxides.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents
Copper

Hazardous decomposition products : Fire may cause evolution of:
Carbon monoxide
Carbon dioxide (CO₂)

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50: 3,000 mg/kg
Species: Rat

: LD50: 1,400 mg/kg
Species: Guinea pig

Acute inhalation toxicity : LC50: 7.36 mg/l , vapour
Exposure time: 8 h
Species: Rat

Acute dermal toxicity : LD50: 3,271 mg/kg
Species: Rabbit

Skin irritation : Species: Rabbit
Result: slight irritation
Method: Tested according to Directive 92/69/EEC.

Eye irritation : Species: Rabbit

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

Result: slight irritation
Method: in vivo assay
Note: According to the classification criteria of the European Union, the product is not considered as being an eye irritant.

Sensitisation : Maximisation Test
Species: Guinea pig
Result: non-sensitizing
Method: OECD Test Guideline 406

Genotoxicity in vitro : Note: Not classified due to data which are conclusive although insufficient for classification.

Genotoxicity in vivo : Test Method: Micronucleus test
Species: Mouse, male and female
Application Route: Intraperitoneal injection
Result: negative

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity effects**

Toxicity to fish : static test
LC50: > 10,000 mg/l
Exposure time: 96 h
Species: Lepomis macrochirus (Bluegill sunfish)

Toxicity to daphnia and other aquatic invertebrates : static test
EC50: > 10,000 mg/l
Exposure time: 24 h
Species: Daphnia magna (Water flea)

Toxicity to algae : static test
NOEC: > 1,000 mg/l

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

Exposure time: 72 h
Species: *Desmodesmus subspicatus* (green algae)

Toxicity to bacteria : EC0: > 10,000 mg/l
Exposure time: 24 h
Species: *Pseudomonas putida*
Method: DIN 38412

Elimination information (persistence and degradability)

Bioaccumulation : Note: no data available

Biodegradability : aerobic
Result: rapidly biodegradable
Value: 63 - 83 %
Method: OECD Test Guideline 301C

Further information on ecology**SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

DOT	UN/ID No.	: UN 1171
	Proper shipping name	: ETHYLENE GLYCOL MONOETHYL ETHER
	Class	3
	Packing group	III
	Hazard Labels	3

IATA	UN/ID No.	: UN 1171
	Description of the goods	: ETHYLENE GLYCOL MONOETHYL ETHER

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

Class : 3
Packaging group : III
Hazard Labels : 3
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355
Packing instruction (passenger aircraft) : Y344

IMDG UN/ID No. : UN 1171
Description of the goods : ETHYLENE GLYCOL MONOETHYL ETHER
Class : 3
Packaging group : III
Hazard Labels : 3
EmS Number : F-E, S-D
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**Inventories**

US. Toxic Substances Control Act : On TSCA Inventory

Australia. Industrial Chemical (Notification and Assessment) Act : On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI) : On the inventory, or in compliance with the inventory

Philippines. The Toxic : On the inventory, or in compliance with the inventory

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

**Substances and Hazardous
and Nuclear Waste Control
Act**

China. Inventory of Existing Chemical Substances : On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand : On the inventory, or in compliance with the inventory

TSCA 12B : US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether) 110-80-5

National regulatory information

US. EPA CERCLA Hazardous Substances (40 CFR 302) : The following component(s) of this product is/are subject to release reporting under 40 CFR 302 when release exceeds the Reportable Quantity (RQ):

Reportable quantity: 1000 lbs

: 2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether) 110-80-5

SARA 302 Components : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components : The following components are subject to reporting levels established by SARA Title III, Section 313:
: 2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether) 110-80-5

SARA 311/312 Hazards : Fire Hazard

CERCLA Reportable Quantity : 1000 lbs

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

California Prop. 65

:



WARNING: This product can expose you to chemicals, listed below, known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

2-Ethoxyethanol (EGEE; 110-80-5
Ethylene glycol monoethyl ether)

Massachusetts RTK

: 2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether) 110-80-5

New Jersey RTK

: 2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether) 110-80-5

Pennsylvania RTK

: 2-Ethoxyethanol (EGEE; Ethylene glycol monoethyl ether) 110-80-5

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 2*	1
Flammability	: 2	2
Physical Hazard	: 0	
Instability	:	0

* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of

2-Ethoxyethanol**128082-1L**

Version 1.1

Revision Date 08/20/2018

Print Date 05/29/2023

the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 10/03/2016

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group