

Lithium carbonate**13010-6X1KG**

Version 1.2

Revision Date 08/29/2023

Print Date 08/30/2023

SECTION 1. IDENTIFICATION

Product name : Lithium carbonate

Number : 000000021112

Product Use Description : Laboratory chemicals

Manufacturer or supplier's details : Honeywell International Inc.
1953 South Harvey Street
Muskegon, MI 49442

For more information call : 1-800-368-0050
+1-231-726-3171(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : **Medical: 1-800-498-5701 or +1-303-389-1414**
: **Transportation (CHEMTREC): 1-800-424-9300 or**
: **+1-703-527-3887**
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : crystalline

Color : white

Odor : odourless

Classification of the substance or mixture

Classification of the substance or mixture : Acute toxicity, Category 4, Oral
Eye irritation, Category 2A

GHS Label elements, including precautionary statements

Lithium carbonate**13010-6X1KG**

Version 1.2

Revision Date 08/29/2023

Print Date 08/30/2023

Symbol(s)

:



Signal word

: Warning

Hazard statements

: Harmful if swallowed.
Causes serious eye irritation.

Precautionary statements

: **Prevention:**

Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves/protective clothing/eye protection/face protection.

Response:

IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/ attention.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula

: Li_2CO_3

Chemical nature

: Substance

Chemical name

CAS-No.

Concentration

Lithium carbonate**13010-6X1KG**

Version 1.2

Revision Date 08/29/2023

Print Date 08/30/2023

Lithium carbonate

554-13-2

100.00 %

SECTION 4. FIRST AID MEASURES

- General advice : Show this safety data sheet to the doctor in attendance.
- Inhalation : Remove to fresh air. If respiratory problems develop, obtain medical attention.
- Skin contact : Wash off with soap and plenty of water. If skin irritation persists, call a physician.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician.
- Ingestion : Do NOT induce vomiting. Rinse mouth with water. Consult a physician.

Notes to physician

- Most important symptoms/effects, acute and delayed : No information available.
- Indication of immediate medical attention and special treatment needed, if necessary : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Carbon dioxide (CO₂)
Dry powder
- Specific hazards during firefighting : The product itself does not burn.
In case of fire hazardous decomposition products may be produced such as:
Lithium oxide
Carbon oxides

Lithium carbonate**13010-6X1KG**

Version 1.2

Revision Date 08/29/2023

Print Date 08/30/2023

Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Wear personal protective equipment. Unprotected persons must be kept away.
Ensure adequate ventilation.
Avoid dust formation.
Avoid breathing dust.
Avoid contact with skin, eyes and clothing.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Do not let product enter drains.

Methods and materials for containment and cleaning up : Use mechanical handling equipment.
Sweep up and shovel into suitable containers for disposal.
Dispose of in accordance with local regulations.

SECTION 7. HANDLING AND STORAGE**Handling**

Precautions for safe handling : Wear personal protective equipment.
Use only in well-ventilated areas.
Avoid inhalation, ingestion and contact with skin and eyes.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.
The product itself does not burn.

Storage

Conditions for safe storage, including any : Store in original container.
Keep containers tightly closed in a dry, cool and well-ventilated

Lithium carbonate**13010-6X1KG**

Version 1.2

Revision Date 08/29/2023

Print Date 08/30/2023

incompatibilities

place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Protective measures : Ensure that eyewash stations and safety showers are close to the workstation location.
Legal requirements are to be considered in regard of the selection, use and care of personal protective equipment.
Avoid breathing dust.
Avoid contact with skin, eyes and clothing.
- Engineering measures : Ensure adequate ventilation, especially in confined areas.
- Eye protection : Safety glasses with side-shields
- Hand protection : Latex gloves
Gloves must be inspected prior to use.
Replace when worn.
- Skin and body protection : Lightweight protective clothing
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

Exposure Guidelines

Contains no substances with occupational exposure limit values.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : crystalline
- Color : white
- Odor : odourless
- Odor threshold : Note: No data available

Lithium carbonate**13010-6X1KG**

Version 1.2

Revision Date 08/29/2023

Print Date 08/30/2023

pH	: ca. 9.0 - 11.0 at 1.00 g/l, 20 °C
Melting point/range	: 720 °C
Boiling point/boiling range	: 1,300 °C
Flash point	: Note: Not applicable
Evaporation rate	: Note: No data available
Flammability	: The product is not flammable.
Lower explosion limit	: Note: Not applicable
Upper explosion limit	: Note: Not applicable
Vapor pressure	: Note: No data available
Vapor density	: Note: No data available
Density	: 2.110 g/cm ³ at 20 °C
Water solubility	: 8.4 g/l at 20 °C
Partition coefficient: n-octanol/water	: Note: No data available
Ignition temperature	: Note: Not applicable
Decomposition temperature	: Note: No decomposition if used as directed.
Viscosity, dynamic	: Note: No data available

Lithium carbonate**13010-6X1KG**

Version 1.2

Revision Date 08/29/2023

Print Date 08/30/2023

Viscosity, kinematic : Note: No data available

Molecular weight : 73.89 g/mol

Bulk density : ca. 450 kg/m³**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.

Conditions to avoid : Avoid dust formation.

Incompatible materials : Strong acids and oxidizing agents

Hazardous decomposition products : In case of fire hazardous decomposition products may be produced such as:
Carbon oxides
Lithium oxide**SECTION 11. TOXICOLOGICAL INFORMATION**Acute oral toxicity : LD50: 531 mg/kg
Species: Mouse: LD50: 525 mg/kg
Species: RatAcute inhalation toxicity : LC50: > 2 mg/l
Exposure time: 4 h

Lithium carbonate**13010-6X1KG**

Version 1.2

Revision Date 08/29/2023

Print Date 08/30/2023

Species: Rat

Acute dermal toxicity : LD50: > 3,000 mg/kg
Species: Rabbit

Skin irritation : Result: No skin irritation

Eye irritation : Result: Irritation to eyes, reversing within 7 days

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity effects**

Toxicity to fish : LC50: 30.3 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates : EC50: > 30.2 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)

Toxicity to algae : EC50: > 400 mg/l
Exposure time: 72 h
Species: Desmodesmus subspicatus (green algae)

Further information on ecology

Additional ecological information : No information on ecology is available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

Lithium carbonate**13010-6X1KG**

Version 1.2

Revision Date 08/29/2023

Print Date 08/30/2023

SECTION 14. TRANSPORT INFORMATION**DOT** Not dangerous goods**TDG** Not dangerous goods**IATA** Not dangerous goods**IMDG** Not dangerous goods**SECTION 15. REGULATORY INFORMATION****Inventories**US. Toxic Substances : On TSCA Inventory
Control ActAustralia. Inventory of : On the inventory, or in compliance with the inventory
Industrial Chemicals (AIIC),
as amendedCanada. Canadian : All components of this product are on the Canadian DSL
Environmental Protection
Act (CEPA). Domestic
Substances List (DSL)

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Existing Chemicals : On the inventory, or in compliance with the inventory
Inventory (KECI)Philippines. Inventory of : On the inventory, or in compliance with the inventory
Chemicals and Chemical
Substances (PICCS)China. Inventory of Existing : On the inventory, or in compliance with the inventory
Chemical Substances
(IECSC)New Zealand. Inventory of : On the inventory, or in compliance with the inventory
Chemicals (NZIoC), as

Lithium carbonate**13010-6X1KG**

Version 1.2

Revision Date 08/29/2023

Print Date 08/30/2023

published by ERMA New
ZealandTaiwan Chemical : On the inventory, or in compliance with the inventory
Substance Inventory (TCSI)**National regulatory information****SARA 302 Components** : No chemicals in this material are subject to the reporting
requirements of SARA Title III, Section 302.**SARA 313 Components** : The following components are subject to reporting levels
established by SARA Title III, Section 313:
Lithium carbonate 554-13-2**SARA 311/312 Hazards** : Acute Health Hazard**California Prop. 65** :  **WARNING:** This product can expose you to chemicals,
listed below, known to the State of California to cause birth
defects or other reproductive harm. For more information go to
www.P65Warnings.ca.gov.
Lithium carbonate 554-13-2**Massachusetts RTK** : Lithium carbonate 554-13-2**New Jersey RTK** : Lithium carbonate 554-13-2**Pennsylvania RTK** : Lithium carbonate 554-13-2**SECTION 16. OTHER INFORMATION**

	HMIS III	NFPA
Health hazard	: 2	2
Flammability	: 0	0
Physical Hazard	: 0	
Instability	:	0

Lithium carbonate**13010-6X1KG**

Version 1.2

Revision Date 08/29/2023

Print Date 08/30/2023

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 08/21/2018

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group